

Article



A Solar Photovoltaic System Applied to Açaí Production and the Development of Riverside Communities in the Amazon

Allan Pena ^{1,*}, Pedro Guedes ², Francisco Malheiros ³, Felipe Monteiro ⁴, Werbeston Oliveira ⁴, Márcio Oliveira ⁴, Gilmar Paixão ⁴, Moisés Sousa ⁴, Geraldo Maranhão ⁴, Alcides Júnior ¹, André Oliveira ⁴, Davi François ⁵, Mary Parmentier ⁶, Marcelino Guedes ^{1,7}, and Alaan Brito ^{1,4}

- ¹ Programa de Pós-Graduação em Ciências Ambientais (PPGCA), Universidade Federal do Amapá (UNIFAP), Macapá 68903-419, AP, Brazil; froesstm@gmail.com (A.J.); marcelino.guedes@embrapa.br (M.G.); aubrito@unifap.br (A.B.)
- ² Escola de Engenharia de São Carlos (EESC), Universidade de São Paulo (USP), São Carlos 13566-590, SP, Brazil; pmlguedes@usp.br
- ³ Associação de Trabalhadores Agroextrativistas da Ilha das Cinzas (ATAIC), Gurupá, PA, Brazil; fran.malheiros2015@gmail.com
- ⁴ Colegiado do Curso de Engenharia Elétrica, Universidade Federal do Amapá (UNIFAP), Macapá 68903-419, AP, Brazil; felipe.monteiro@unifap.br (F.M.); wdoliveira@unifap.br (W.O.); marcioclei@unifap.br (M.O.); gilmar.paixao@unifap.br (G.P.); sales.moises@unifap.br (M.S.); maranhao@unifap.br (G.M.); andreof@unifap.br (A.O.)
- ⁵ Karlsruhe Institute of Technology (KIT), Institute for Technology Assessment and Systems Analysis (ITAS), 76133 Karlsruhe, Germany; davi.francois@kit.edu
- ⁶ School for the Future of Innovation in Society, Arizona State University (ASU), Tempe, AZ 85281, USA; mj.parmentier@asu.edu
- ⁷ Empresa Brasileira de Pesquisa Agropecuária (EMBRAPA), Macapá 68903-419, AP, Brazil
- Correspondence: aglpena@unifap.br

Abstract: Energy exclusion in the Amazon imposes barriers to the socioeconomic development of riverine communities, affecting the açaí value chain. Photovoltaic solar energy is a promising solution; however, its insertion in isolated communities with a focus on strengthening the açaí chain is still a challenge. This research aims to use photovoltaic solar energy as an integration mechanism for productive activities and a better quality of life for riverside families in the Brazilian Amazon. This study was conducted in the Ilha das Cinzas Community, in Gurupá/PA, starting with a rapid participatory diagnosis to understand the characteristics of the families. Strategic planning using the SWOT methodology was used to define action plans to enhance the insertion of solar technology. A new photovoltaic system configuration adaptable to the energy demands of families, capable of meeting both daily and motor loads was developed. In addition, the action plans included training residents and the sharing of experiences with other communities, ensuring greater success in technology transfer. This study demonstrates that the socioeconomic development of riverine communities can be achieved through the insertion of new technologies adapted to their reality, accompanied by the participation and training of the actors involved.

Keywords: renewable energy; electrical exclusion; access to basic services; participatory diagnosis; strategic planning; adaptable configuration; technology transfer; training of residents

1. Introduction

1.1. Electricity and Socio-Economic Development

Electricity is indispensable for the development of modern communities. The conduct of basic day-to-day activities such as education, health, entertainment, transportation, food,



Academic Editor: Gilles Notton

Received: 27 December 2024 Revised: 5 February 2025 Accepted: 19 February 2025 Published: 11 March 2025

Citation: Pena, A.; Guedes, P.; Malheiros, F.; Monteiro, F.; Oliveira, W.; Oliveira, M.; Paixão, G.; Sousa, M.; Maranhão, G.; Júnior, A.; et al. A Solar Photovoltaic System Applied to Açaí Production and the Development of Riverside Communities in the Amazon. *Sustainability* **2025**, *17*, 2447. https://doi.org/10.3390/ su17062447

Copyright: © 2025 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/ licenses/by/4.0/). and leisure are always related to this resource [1]. In addition, more complex activities such as those developed in the industrial sector depend on the availability of electricity on a large scale.

"Clean and Affordable Energy" is one of the Sustainable Development Goals (SDGs) established by the United Nations (UN) to be achieved by the year 2030, "which it is a reflex of increased concern about unsustainable energy practices and potential effects on vulnerable community groups" [2]. This SDG is strongly linked to other objectives [3], which can be achieved more effectively with access to electricity, such as "Zero Hunger and Sustainable Agriculture" (SDG 2), where energy holds a vital role in every step of plantation production and distribution [4,5]; "Drinking Water and Sanitation" (SDG 6), which shows an evident interdependence with focuses on ensuring the availability and sustainable management of water and sanitation [6]; and "Sustainable Cities and Communities" (SDG 11), a goal where success relies on integrating clean energy solutions into urban planning [7].

However, despite the development potential provided by electricity, almost 1 million people in the area covered by the Brazilian Legal Amazon do not have access to electricity, even though there is a legal basis for the universalization of this resource [8]. This situation is one of the barriers that hinders the development of several value chains in the region, such as açaí (*Euterpe oleracea* Mart.), consequently affecting Amazonian extractive communities [9].

The açaí production chain has great social and economic value in the Amazon region. According to the Recommendations for Systemic Impacts on the Açaí Value Chain [10], the world market for the fruit produces about BRL 720 million per year, where in Brazil alone it is estimated that the annual production value is BRL 6 billion. In the Amazon region, this industry plays a crucial role in generating income and promoting food security, involving more than 300,000 people, including 150,000 families.

The state of Pará, the world's largest producer of fruit and pulp, produces approximately 53% of the quantity sold worldwide: in 2019 it handled about BRL 3.7 billion. In addition, açaí pulp is consumed daily by riverside families (those who live on the banks of rivers), and this food is one of the things responsible for the low rates of food insecurity in certain communities, such as Ilha das Cinzas [11].

Most of Brazil's states are connected to the National Interconnected System (SIN (Sistema Interligado Nacional)), a complex system that interconnects generating sources to consumption centers throughout the country. Demands not connected to the SIN are met by Isolated Systems (SISOL (Sistemas Isolados)), of which 98% are fuel generators. However, it is a source of electricity that involves several problems, such as pollution and emission of greenhouse gases (GHG). In addition, recurring maintenance, dependence on the fluvial transport of fuel, and high costs, are recurring examples. Many communities are not served by SIN or SISOL. Communities located in remote regions with populations dispersed over a large area, are served by small decentralized generating sources, usually fuel generators.

1.2. Photovoltaic Solar Energy Technologies in the Amazon

In this scenario, the açaí value chain is restricted to the fruit extraction, with no processing and, as a consequence, with no added value to the final product. Therefore, photovoltaic solar energy is highlighted as a renewable source with many advances in the last decade regarding ways to "reduce prices while increasing conversion efficiency in a variety of modules designs, including crystalline, thin-film, and organic-based systems" [12]. Recently, Perovskite Solar Cells (PSCs) have shown significant promise in this field, but with some issues with regard to commercial viability. Despite high efficiency and low manufacturing costs, the use of lead in their composition and their stability under high temperature and humidity conditions are critical factors for their deployment in the Amazon [13].

The Brazilian territory presents great potential for this renewable source and has received several tax incentives over the years [14,15], which has enabled a rising market with well-developed technologies to grow. The average daily irradiation in the horizontal plane over a year across Brazil varies significantly by region and season due to the continental dimensions of the country, but has significant photovoltaic potential, ranging from 4.2 to 6.2 kWhm⁻², where the higher values are in the northeast region [16].

Photovoltaic generation systems have come to play an important role in universalizing access to electricity through the federal Light for All (LpT (Luz Para Todos)) program, due to its association with renewable energy, continuous technological advances, rising popularity, and capacity of isolated generation, which enabled the installation of photovoltaic (PV) systems in communities with favorable characteristics for this type of generation [17].

In addition, from Normative Resolution (NR) No. 493/2012 of the National Electric Energy Agency (ANEEL (Agência Nacional de Energia Elétrica)), later replaced by NR No. 1000/2021 and No. 1059/2023, procedures and conditions of supply were established through Isolated Microsystems for Generation and Distribution of Electric Energy (MIGDI (Microsistemas Isolados para Geração e Distirbuição de Energia Elétrica)) or Individual Systems for Generation of Electric Energy with Intermittent Source (SIGFI (Sistemas Individual para Geração de Energia Elétrica com Fontes Intermitentes)) [18].

For communities far from urban centers, Isolated Photovoltaic Systems (IPS) have characteristics well suited to these surroundings, and may assume different configurations. The most common of these is the Domestic Photovoltaic System (DPS), used to meet everyday demands: televisions, lighting, refrigerators, appliances, pulpers (popularly called "mixers") of açaí, motor pumps, etc.

An important component in DPS is the voltage inverter, responsible for converting direct current power to an alternating current. It is an element sensitive to overloads, a frequent cause of damage. Some systems serve loads with single-phase motors driven with a direct start, causing a momentary peak of power that results in a voltage drop much higher than the limits established in standards which causes operational disturbances not only in the inverter, command, and protection equipment [19], but also affects the motor performance, reliability, and longevity [20].

Studies on the dimensions and economic feasibility of domestic systems have been carried out in the Amazon region. In the riverside housing of Manacapuru, a comparative study was carried out between a DPS and a diesel generator [21] and in the Nova Esperança community in the Cuieiras River which received 957 W and two-day autonomy standalone systems [22]. Other studies showed similar results of economic viability for different DPS sizes in different Amazonian locations: Santarem and Ilha das Onças, both locations in the state of Para [23]. Recently, research has proposed the development of modular photovoltaic solar energy kits, with the capacity to be expanded according to demand [24].

Another IPS configuration is the Direct Coupling Photovoltaic System (DCPS), specifically developed to operate with motors, an essential tool for processing açai, a procedure that consists of inserting the fruits into a metal tank with a mobile shaft coupled to the motor shaft in order to separate the pulp from the fruit seeds. In this scheme, the Variable Speed Driver (VSD) is an example of power conditioning equipment that can be used, as it is specifically designed to operate three-phase induction motors. By default, the VSD requires high input voltage values, which requires the open circuit voltage of the Photovoltaic Array (PVA) modules to be within the limits of the VSD.

This configuration does not include an energy accumulator, one of the factors that increase systems costs, so the rotation speed of the machine varies with the availability of

solar incidence. The machine is started gradually, avoiding current surges. In addition, VSDs are found in a wide range of power for different prices and with national manufacture and maintenance. In recent decades, many works have been developed aimed at the application of VSDs in photovoltaic pumping systems, an application of DCPSs.

One of the papers presents a system that employs a maximum of four photovoltaic panels, a DC-DC step-up converter, a standard frequency converter, and a 1 HP water pump [25]. Another performs the configuration used in this research: a VSD powered by solar panels, which simplifies the system architecture, reduces losses, and improves overall performance [26]. More recently, a piece of research has made a comparative simulation of two DCPSs with parallel VSDs, where in one system, each VSD has a PVA and in the other system both VSDs are energized by a single PVA [27].

There are works that focus on the use of DCPSs in rural applications, evaluating the sharing of a DCPS used for pumping water and additionally a cassava grater [28] or the development of a technology aimed at the use of an açaí pulper from the energy provided by a DCPS (photovoltaic pulper), research that highlights the role of VSD in conditioning the DC power generated by PVA to drive a motor coupled to an açaí pulper [29].

Many of these technologies that use photovoltaic solar energy are classified as social technologies, as they are developed in interaction with the community in search of solutions related to existing social problems [30], adapted to the reality of families, places, customs, culture, etc. Such technologies, unlike conventional ones, allow a more inclusive and sustainable solution, although not as efficient.

Considering the context of energy exclusion in riverine communities in the Brazilian Amazon, the capacity for change that access to electricity allows, the solar potential for electricity generation in the region, and the different configurations and technologies of photovoltaic solar energy, this research proposes the insertion of solar energy technologies in a riverine community as an integration mechanism between existing electrical demands, productive activities in the açaí value chain, and present social technologies.

The hypothesis of this research is that a system with versatile and flexible topology, which considers the weaknesses and welfare needs of the community, can contribute to the development of the community by strengthening the açaí value chain and integrating the demands of families (domestic and productive).

2. Materials and Methods

The study area selected was Ilha das Cinzas, a riverside community located in the estuary of the Amazon River in the territory of Marajó. Despite being part of the state of Pará, the island (as well as several others in the region) has closer commercial relations with the cities of the state of Amapá, mainly with Mazagão, Santana, and Macapá, due to the distance from these urban centers, as shown in Figure 1. The community is characterized by its dependence on the açaí value chain and faces significant challenges related to energy exclusion and socioeconomic development.

To obtain information about the community, Participatory Rapid Diagnosis (PRD) was performed [31] throughout 2021 and partially in 2023. It is a tool that allows the author to contact the agents involved and participate in the problem situation. To perform the PRD, information from a form prepared and applied by the Association of Agroextractivist Workers of Ilha das Cinzas (ATAIC (Associação dos Trabalhadores Agroextrativistas da Ilha das Cinzas)) was used. It addressed several aspects of the daily lives of families in the community:

- General aspects of the family;
- Availability of electricity;
- Source of electricity used (if available);

- Number of daily hours of electricity available;
- Use of electricity for income generation;
- Water treatment;
- Sanitary sewage.





In addition to the form, data were collected from community research and field observations, vital for comparisons with the results obtained by the other two forms of data collection.

To analyze the information obtained from the PRD, a SWOT analysis (Strengths, Weaknesses, Opportunities and Threats) was carried out, a tool that was initially only used in business and industrial environments, but that nowadays it is often used as a strategic mechanism for the elaboration of action plans in different situations, such as in isolated communities [32–34].

This research was carried out in two stages. In the first, internal and external factors were highlighted according to the information obtained in the PRD. These factors were scored from 1 to 5 according to their "importance" (F_{ip}), "intensity" (F_{it}), and "trend" (F_t). In the case of external factors, the "trend" factor is replaced by "urgency" (F_u). The final score (P_F) of the factor is given by multiplying these elements (1):

$$P_F = F_{ip} \cdot F_{it} \cdot F_t \tag{1}$$

In the second stage, the five factors of each quantity of the SWOT matrix were separated and placed in an electronic questionnaire format via Google Forms. Members of ATAIC, members of partner institutions of the association, and residents who actively participate in the organization of the community, but who are not part of the administration of ATAIC, were chosen. Each of these people scored the pre-established factors for calculating an average and obtaining the final SWOT matrix. In possession of this matrix, the factors were crossed in order to define the best strategy to be adopted: offensive, defensive, reinforcement, or confrontation. From the crossings, it was possible to carry out a grouping with the objective of using the same action plan aimed at different crossings of factors. The action plans focused on four main problem situations, highlighted in the later section.

3. Results and Discussions

This topic will present the results obtained by the research in four parts. Each subtopic presents a discussion in sequence with the demonstration of the results. The first shows the main information obtained from the questionnaires applied in the community by ATAIC. The second topic describes the SWOT analysis formed from the main factors obtained from the questionnaires, bibliographic studies, and field observations. Based on the SWOT analysis, four action plans were developed, focused on the intersections between factors, giving rise to the third topic that presents one of the main contributions of the research: a photovoltaic system used to meet both domestic demands and production demands using two different configurations from the same arrangement of modules. Finally, the fourth topic presents the results obtained from the third and fourth action plans: training and qualification of community residents and sharing the results of the project with other communities in the region.

3.1. Participatory Rapid Diagnosis

Ilha das Cinzas is one of the first locations in the state to have an Agroextractivist Settlement Project, created as a "way to recognize the importance of riverside dwellers for the protection of local biodiversity", as well as for the maintenance of ways of life and socioeconomic and cultural reproduction [11]. It is a community, as observed in Figure 1, where the only possible means of transport is fluvial. Like several communities in the region, it has great logistical challenges in acquiring daily resources and essential services such as health, education, and electricity.

The PRD was carried out with the application of 68 forms per family during 2021. It was ratified that açaí is part of their source of income, with other complementary sources of income—20 families that did not fill in the field for this answer. Of the 48 responding families, 19 (39.58%) depend exclusively on açaí extraction, a similar result to that found in the research by [35]. As for access to electricity, Figure 2 summarizes the information that was obtained.



Figure 2. Number of households with access to electricity.

It was possible to identify scenarios in which the same photovoltaic system or the same generator was used to serve more than one family. Similarly, some families have both a photovoltaic system and a generator. Of the 44 families that had generators to have access to electricity, 31 depended exclusively on this energy source. Similarly, of the 28 families that used solar energy, 15 depended exclusively on this form of electricity generation. Consequently, 13 families had the two sources of electricity generation previously highlighted.

Commonly, children build houses near their parents' homes in order to share energy. This situation is a potential problem, not only in Ilha das Cinzas, but in other communities as well, since this increase in demand is not foreseen and, in the case of photovoltaic systems, generates an overload in the inverter, which is one of the main causes of burns and failures of this equipment, as it is not common for protective devices to be present in the installation.

An important issue raised in the form was the use, or not, of electricity in some productive activity developed by the family. Of the 52 families who answered the question "Does the family use any form of solar energy or diesel generator engine in any production process that generates income for the family?", 44 pointed out that they did not use it. This situation reflects how the energy exclusion of the community is a barrier to the economic development of families, who invest in their own electricity generation systems to first meet their daily demands and improve their quality of life.

The form also provided information on the main energy demands that were desired to be met with the purchase of a PV system (highlighted in Figure 3). The main demand is for lighting, followed by food refrigeration, leisure activities, use of the açaí pulper, and communication. These are loads common to all residents and should be considered when sizing any type of power generation.



Figure 3. Appliances in homes.

Of the 68 families, 47 indicated that they had at least one açaí pulper in their home and 36 had a freezer, two essential loads for the açaí value chain. This demand for energy, directly linked to the self-consumption and food sovereignty of families, is directed to the well-being of people in the communities, as income generation occurs from the commercialization of açaí fruits and not from the pulp.

Another recurring demand in homes is for water pumps (40 families had them). Because they are stilt houses, the residences are relatively far from the river, so motor pumps are used to collect water from the river to a reservoir near the residence. However, water treatment is a problem in many families. It was identified that 33 of the 68 families apply the combination of chlorine and hypochlorite to treat water used in household tasks and some even for consumption. The problem in this matter is in the dosage of the product, since during field trips many families reported not having a measurement parameter for the use of chlorine and/or hypochlorite mixed with water.

Another characteristic of the community that must be carefully observed is the destination of the sewage of the residence. The responses to the forms showed that 47.04% (32) of the families dump the sanitary sewage directly into the floodplain near the toilets. This, added to the movements of the tide and the incorrect treatment of water can result in various health problems for families.

In some residences of Ilha das Cinzas (more precisely six), there were already biodigester septic tanks installed as an alternative sanitary sewage system (ASSS). This structure is of interest to the work presented here because its final product is a liquid resulting from the anaerobic decomposition of human waste that can be used as a biofertilizer in plantations near the ASSS. The construction of this biodigester is simple and low-cost. It can attend a household of up to five people [36] and it is already known that the liquid helps in the growth of plants, improving aspects of stem weight and leaf weight in cabbage seedling plantations [37].

3.2. SWOT Analysis

The final SWOT matrix, after performing the steps presented in the methodology, can be seen in Table 1. Here, it is important to highlight how in addition to the "Strength", all other factors have undergone changes in the general order, which ratifies how both the DRP and the SWOT analysis should be carried out in the most participatory way possible within a given methodology, as it is the active agents of the community that can highlight the problem situation with greater clarity.

Table 1. Five factors with the highest scores for each element of the SWOT analysis.

Top 5—Internal Factors					
Strengths	Weaknesses				
1—There is a well-organized and qualified Workers' Association to access external resources;	1—Pests and diseases in açaí plantations and shrimp;				
2—Participation in projects with national and international financing;	2—Deficiency in the educational system;				
3—The goals of universal access to electricity and sanitation in communities are being anticipated;	3—Predatory practices (garbage burning, overfishing, "açaization" (process of deforest native vegetation to make priority space for acaí plantations), etc.):				
4—Availability of training courses for families;	4—Difficulty in training new leaders;				
5—Uses the açaí value chain as the main source of income.	5—Rationing of electricity.				
Top 5—External Factors					

I I					
Opportunities	Threats				
1—Açaí market on the rise;	1—Açaí market on the rise;				
2—Rising of the market focused on	2—Rising of the market focused on				
bioeconomy and environmental services;	bioeconomy and environmental services;				
3—Science and technology institutions	3—Science and technology institutions				
(STIs) operating in the region;	(STIs) operating in the region;				
4—National/international notices for	4—National/international notices for				
universal access to electricity and basic	universal access to electricity and basic				
sanitation;	sanitation;				
5—Rising photovoltaic solar energy	5—Rising of photovoltaic solar energy				
market.	market.				

One factor mentioned by the agents was the potential of the community in the development of new value chains, especially in the face of Weakness 1 of Table 1, since a dependence on the açaí value chain can put families in a vulnerable situation in the face of an eventual crisis in this production.

The next stage of the SWOT analysis was the crossing between the factors to define the type of strategy that would be elaborated and later the action plans, as observed in Table 2. It was observed that, after the crossings, the same action plan could be implemented for different crossings, even for different types of strategies.

Strengths and Weaknesses	Factor	Opportunities and Threats	Factor	Type of Strategy	Action Plan
(W5) Rationing of electricity.	Weakness	(O5) Rising photovoltaic solar energy market.	Opportunity	Reinforcement strategy	(1) Use photovoltaic solar energy as an energy source to strengthen other
(S5) Uses the açaí value chain as the main source of income.	Strength	(O1) Açaí market on the rise.	Opportunity (Offensive strategy	links in the acaí value chain within the community. Seek technologies that enable the use of different types of loads for different applications.
(S5) Uses the açaí value chain as the main source of income.	Strength	(O5) Rising photovoltaic solar energy market.	Opportunity	Offensive strategy	
(W1) Pests and diseases in açaí trees and shrimp.	Weakness	(O5) Rising photovoltaic solar energy market.	Opportunity	Reinforcement strategy	(2) Use photovoltaic solar energy as an energy source for the development of complementary value chains. Develop a versatile technology capable of meeting the demands of the açaí chair and loads from other value chains.
(W1) Pests and diseases in açaí trees and shrimp.	Weakness	(T1) Climate crises (increased temperature, reduced rainfall, thunderstorms, cyclones, etc.)	Threat	Strategy for defense	
(W1) Pests and diseases in açaí trees and shrimp.	Weakness	(O1) Açaí market on the rise.	Opportunity	Reinforcement strategy	
(S4) Availability of training courses for families.	Strength	(O3) STIs operating in the region.	Opportunity	Offensive strategy	(3) Provide training courses in renewable technologies for families in the
(W2) Weaknesses in the education system.	Weakness	(O3) STIs operating in the region.	Opportunity	Reinforcement strategy	community. Courses should approach theory in a didactic and accessible way and use practices to fix knowledge.
(W4) Difficulty in training new leaders	Weakness	(T5) Lack of well-organized communities in the region.	Threat	Strategy for defense	(4) Share ATAIC's experiences with Ilha
(W4) Difficulty in training new leaders	Weakness	(O3) STIs operating in the region.	Opportunity	Reinforcement strategy	other communities to understand the process. Hold conversation circles, events with ATAIC partners, and lectures, among other ways to socialize knowledge.
(S1) There is a well-organized Workers' Association that is able to access external resources	Strength	(T5) Lack of well-organized communities in the region.	Threat	Confrontation strategy	U

Table 2. Result of the crossing of the main factors. They were grouped according to their relationship with each of the four action plans prepared.

Action Plan 1 (AP1) sought to develop other links in the açaí value chain within the Ilha das Cinzas community. With the açaí market on the rise (O1) and the rising solar energy sector (O5), it is important to increase community forces (a well-organized workers' association—S1; the familiarity of families with this value chain—S5) to take advantage of opportunities.

Most families in the community are part of the açaí production link. For the development of other links (processing and sale in mixers), it is necessary to confront weaknesses such as energy rationing (W5). The rising market for solar photovoltaic energy (O5) is The development of a technology capable of strengthening the açaí value chain using photovoltaic solar energy technologies through partnerships with these STIs is one possible route. However, the technology should not focus only on productive activity, it should be able to meet the daily demands of families and meet loads from productive activity: açaí pulper, pulp refrigeration, açaí irrigation, pumping and water treatment, existing social technologies such as bio digesting tanks, among others that may be necessary.

Action Plan 2 (AP2) is complementary to AP1. As previously stated, most families in the community use the açaí value chain as their main source of income. Relying exclusively on a single source of income, in the scenario of climate crises as a threat (T1) and pests and diseases in acai trees (W1), can be dangerous.

Thus, the development of a technology that uses solar photovoltaic energy (O5), not only to strengthen the açaí value chain but also to allow the development of other complementary productive activities, is of great importance.

Objectively, photovoltaic solar energy technology must be versatile and capable of integrating different demands: the daily lives of families, the açaí value chain, and other productive activities that can be developed by families.

Action Plan 3 (AP3) focused on family training activities—mainly young people seeking possible new professions since the local educational system is deficient (W2).

As much as an advanced technology is developed and implemented in the community, without the participation and communication with families, the implanted technology tends to become "distant" and, consequently, "strange" if it does not have technical monitoring. The transfer of technology to isolated communities without the training of its members is bound to fail, as it is a process that involves both technical and social aspects.

To this end, during the stages of implementation of PV system in the community, the residents and their families always followed the process and often participated in an auxiliary way in the installation of the components. In addition, with the help of the partner STIs (O3), a theoretical and practical mini course was delivered, open to the public (without age, sex, or gender restrictions), on the basic concepts of electricity and components of photovoltaic systems.

Finally, Action Plan 4 (AP4) focused mainly on sharing experiences and knowledge acquired not only by ATAIC, but by all partner agents. As there is a lack of well-organized communities (T5) such as Ilha das Cinzas in the region and the community itself finds it difficult to train new leaders (W4), it was essential to organize an event that could bring together key agents to share information on the successes and adversities of the project.

In view of the factors chosen and the intersections between them, the business spreadsheet used in the SWOT analysis reported that the favorability index, that is, how favorable is the situation of the riverside community of Ilha das Cinzas, to be 51%, which corresponds to the concept "Favorable". Considering the correct SWOT analysis, it is necessary to maintain what is being done in the community and add actions to improve strengths and take advantage of opportunities, in addition to measures to contain possible weaknesses and threats. Thus, it is possible to infer that the community is in a favorable situation.

3.3. Mixed Configuration Photovoltaic System

Based on AP1 and AP2 from Table 2, it was possible to define that photovoltaic solar energy technology should be developed to integrate diverse types of loads into different applications. The system needed to be flexible, allowing changes in its configuration, and adapted to the reality of families. To meet domestic loads, the most indicated PV system is the DPS. For productive activities that use driving loads, an appropriate topology is DCPS with VSD. However, acquiring photovoltaic modules for the two systems separately would make the project more expensive. Therefore, a new topology was developed, where the same PVA was used to energize either the DPS or the DCPS. For this new way of connecting two subsystems to the same array, the name of Mixed Configuration PV system (MCPS) was given.

According to the Amapá State Solar Energy Atlas, one of the most recent sources of solar potential data the region near Ilha das Cinzas has global daily irradiation in the horizontal plane in the range between 4.8 kWhm⁻² and 5.4 kWhm⁻² [38]. For the sizing of the DPS PV array, an estimate of daily consumption per family was considered, considering the household appliances most mentioned in the form (Figure 3).

From a more conservative point of view, the dimensioning followed the criterion of adopting the lowest-value Peak Sun Hours (PSH—a parameter that relates the average irradiance measured in a monthly time interval and translates it into a number of hours equivalent to 1000 Wm^{-2}) in the region, thus ensuring that the system will meet the loads even in periods of lower irradiance. The estimated total daily consumption was 3.59 kWh. Considering this demand (*L*) and the PSH parameter equal to 4.8 h, the peak power of the PVA (*P*_{PVA}) can be obtained to meet a certain family by using Equation (2):

$$P_{PVA} = \frac{L}{PSH \times RF_1 \times RF_2} \tag{2}$$

where RF_1 and RF_2 are power reduction factors related to losses due to external effects and electrical losses, which assumed values equal to 0.75 and 0.9, respectively, because they are standard values in the literature (they can and should be changed according to necessity). Therefore, substituting the values mentioned in Equation (2), the PVA-installed peak power required to attend a daily household demand of 3.59 kWh is 1.11 kW_P .

For the DCPS PV array, motor loads of up to 1.5 HP (approximately 1.104 kW) were considered. On average, three-phase induction motors have an efficiency (η) of approximately 85%. Therefore, the peak power of the PVA to meet this demand is (3):

$$P_{PVA}(W_P) = P_{in} \times 85\% + P_{in} = 1.104 \text{ kW} \times 85\% + 1.104 \text{ kW} = 2.04 \text{ kW}$$
(3)

For the design of the following systems, the technical data of the 72-cell polycrystalline module model MS320 from the manufacturer MinaSol (Araguari, Brazil) were considered. It is important to emphasize that the choice of components and technologies used in the research was strongly influenced by logistics and local availability. Due to the geographical distance of the region from large commercial centers, many pieces of equipment are not available in the state.

The module data (Table 3) under standard irradiance and temperature conditions (1000 W/m² and 25 °C, respectively) were used in simulations for operating conditions closer to the Amazonian reality: module temperature equal to 60 °C and irradiance equal to 1200 Wm⁻².

Thus, considering the module with 320 W_P of peak power, the number of PV modules (*NM*) for the DPS can be calculated using (4):

$$NM = \frac{P_{PVA}(W_P)}{P_{MS320}(W_P)} = \frac{1.11 \ kW_P}{320 \ W_P} = 3.4 \cong 3 \tag{4}$$

Technical Specifications (STC)					
Nominal Power	320 W				
Maximum System Voltage	1000 V				
Maximum Power Voltage (V _{MP})	37.1 V				
Maximum Power Current (I _{MP})	8.63 A				
Open Circuit Voltage (V _{OC})	45.7 V				
Short Circuit Current (I _{SC})	9.04 A				
Operating Temperature	$-40~^\circ\mathrm{C}$ a $80~^\circ\mathrm{C}$				

Table 3. Standard technical specifications (1000 Wm⁻², 25 °C, 1 ms⁻¹, 1 AM) of the photovoltaic module MS320 from the manufacturer MinaSol. Source: [39].

For the DCPS, the following calculation was necessary (5):

$$NM = \frac{P_{PVA}(W_P)}{P_{Mdulo}(W_P)} = \frac{2.04 \ kW_P}{320 \ W_P} = 6.37 \cong 6 \tag{5}$$

Therefore, to use the same set of panels to serve two subsystems that require different energy levels, the largest quantity required as a reference was used: six photovoltaic modules. As will be observed in the following text, the DPS and DCPS configurations operate with different arrays of modules, so a switching system that would allow the PVA to be used to energize the DPS and to energize the DCPS was necessary.

The switching system, detailed below, is based on the use of three-position switches: position 0 being null, where there is no circulation of electric current, and positions 1 and 2 corresponding to DPS and DCPS, respectively. The was no experimental installation prior to field activities. The process of system sizing was carried out and physical installations were made. During this process, a TRMS digital multimeter model EM6000 with a measurement category CAT II 600 V and pollution degree 2 was used.

3.3.1. Domestic Photovoltaic System

As the number of modules was defined as six, for the DPS they were associated in order to respect the voltage and current limits of the controller. The system uses the TRIRON4210N controller from the manufacturer EPEVER (Beijing, China), which has an input voltage limit of 90 V_{DC} to 100 V_{DC} .

Thus, as the modules have an open circuit voltage equal to 45.7 V (Table 3), the maximum number of modules in series is two. As there are six modules, the remaining four modules assume the association of two pairs in series and finally the three pairs in parallel (diagram on the left in Figure 4).

Simulations of the characteristic curves of the AFVs were performed in different configurations according to the needs of each subsystem. The simulations were carried out in the Crearray V.03, a software developed originally in 1993 using MS-DOS, later reconstructed in Visual Basic for Windows and used to estimate I–V curves from photovoltaic cells, modules or arrays, obtained from a mathematic model [40]. With this software was possible to compare the curves I–V under standard test conditions and in conditions closer to the Amazonian reality (graph on the right Figure 4).

In the DPS, it is possible to use loads in alternating current (AC) and direct current (DC). The AC bus works from a power inverter connected to the energy accumulator (lead-acid battery bank). The DC bus works from a charge controller output at 24 V.

The use of a DC circuit is advantageous because, even in the event of a failure or eventual burning of the voltage inverter, the system will not be idle. In the pilot system, presented in a work by [41], the DC bus energizes a 72 L freezer and a lighting circuit with LED lamps. To use this subsystem, switching must be performed by turning the switches (detailed below) to position 1, as noted in Figure 5.



Figure 4. Association of three arrays of two modules in series from PVA to DPS; Crearray simulation of curve I–V from PVA to DPS under conditions closer to Amazon reality (module temperature of 65 °C, irradiance of 1200 $W.m^{-2}$).



Figure 5. A domestic photovoltaic system used to attend daily domestic electrical demands in households of Ilha das Cinzas; this subsystem is connected to the PVA only when changing the positions of the switches to 1, thus changing the configuration between the modules.

After installing the system, it was observed that the charge controller has a limitation on the power used. As it has a nominal charge and discharge current limit of 40 A, connected to a 24 V energy accumulator, the maximum power that the controller is capable of managing is 960 W—only half of the installed power of the PVA. The author's leave as future contributions the possibility of either changing the voltage of the energy accumulator to 48 V (four batteries in series) or replacing the charge controller with one with a greater capacity to use all of the power generated by the PVA.

3.3.2. Direct Coupling Photovoltaic System

The DCPS consists of the direct connection of the PVA to the VSD that drives the desired driving load. The VSP model IVS100 of the manufacturer INTEGRALTEC (Porto Alegre, Brazil) was used. This model supports 220 V three-phase machines up to 1.5 HP. It is important to highlight that, despite having the operating characteristics of a VSD, the component in question is marketed under the name of "solar energy frequency inverter for

motors", as it has technical specifications characteristic of a VSD used to drive motor loads from a solar energy source.

As mentioned, VSDs commonly operate with high voltage values. The model used in this work is one of them. Among the options available in the product instruction manual, there is the configuration of six 320 W_P photovoltaic modules in series [42] (top diagram on Figure 6). For the configuration of this subsystem, the simulation of the necessary PVA was also performed, as observed in the lower graph of Figure 6.



Figure 6. Connection of the six modules in series that make up the DCPS PV array; $I \times V$ curve of the PVA used in the DCPS.

From the values defined for the PVA, it is necessary to configure the VSD through the six on–off switches (DIP switches). They are configured according to the power of the arrangement, the machine to be used, and the reconnection time in cases of undervoltage, among other parameters. A work by [41] presents the table with the settings used. To use the DCPS subsystem, it is necessary to switch the switches to position 2, as shown in Figure 7.



Figure 7. Direct coupling system used in electrical demands that relies on driving loads in productive chains, especially the açaí pulper. This configuration is connected to the PVA only when changing the position of the switches to position 2, thus connecting all the modules in a series array.

3.3.3. Switching System

As for both DPS and DCPS, two modules are used in series; the PVA has three pairs of two modules in series, and it is necessary to extend the six terminals to the switchboard where the switches are fixed. In this framework there is a positive and a negative, both resulting from the serial connection of every two modules and then fixed in a connection bar (Figure 8).



Figure 8. Switching system configuration used: (a) modules connected to the fixed bar in order to avoid accidents and current leaks; (b)switches fixed to a switchboard for better organization and safety of conductors and system users.

To perform the switching between the DPS and DCPS subsystems, two three-pole switches of the model K356-40 from the manufacturer Metaltex (Genestrerio, Switzerland) were used. The six resulting terminals of the PVA fixed to the connection bar are connected to the switches—as they are tripolar, each switch connected to three terminals. The remaining serial and parallel associations are performed at their outputs, located at the top. The terminals resulting from these associations are then fixed in a connection bar from where the load controller and the VSD, related to the DPS and DCPS, respectively, will be connected. For the DPS, the two transfer switches are switched to position 1. As the serial connections have already been made and the resulting terminals have been connected to the switches, the next step was to perform the connections in parallel, that is, to interconnect all the positive and negative terminals, resulting in two conductors, one positive and one negative, that are connected to the DPS (Figure 9).



Figure 9. Parallel association of the terminals resulting from the PVA to assume the necessary configuration for the DPS.

In Figure 10, the series associations are made by connecting poles 7 and 11 of the first switch (left side) and poles 7 and 3 of the second (Figure 9). After the serial associations are made, the resulting positive (pole 3 of the first switch) and negative (pole 11 of the second switch) terminals are then fixed to the connection bar from where they are connected to the DCPS variable speed-drive.



Figure 10. Series association of modules for connection to the DCPS VSD.

The switches receive six terminals from three associations of two pairs of photovoltaic modules. Once the remaining associations have been carried out, as detailed above, it is possible to use the switches to switch between the systems as required. By placing them in position 1, the PVA assumes the association of three connections of two modules in series and energizes the DPS, thus charging the battery bank. In position 2, the two switches connect the PVA terminals in the association of the six modules in series, thus energizing the DCPS that activates a three-phase induction motor for the development of some productive activity. Finally, the integrator system that has a PVA with a mixed configuration according to the need of the subsystem is summarized in Figure 11.

The switching system is operational and fulfills its purpose, however one of the gaps in the project concerns the monitoring of the mixed configuration systems installed. In total, there were four systems with this configuration; however, without acquisition of operating data. A necessary improvement in the future is the insertion of a local or remote monitoring mechanism for the subsystems, both domestic and productive.



Figure 11. Complete mixed configuration photovoltaic system where the area delimited by the yellow dashed rectangle corresponds to the DPS, responsible for mainly meeting the family's daily domestic demands; and the area delimited by the blue rectangle corresponds to the DCPS, responsible for activating driving loads through the VSD, with the açaí pulper being the main load to be met, though it can be used for other production demands that require a three-phase motor.

3.4. Training and Socialization of Knowledge and Experiences

As defined in AP3, the importance of training community families—especially young people—was highlighted. Throughout the process of implementing PV systems in the community, there were residents actively participating in the project. Even in situations where they would not be the ones benefiting from the installation of the system, they showed interest and participation in learning not only the principles of operation of the system components but also the practical execution of the installation.

In addition to monitoring the installation of systems, the community participated in a training held at the ATAIC headquarters, with a focus on presenting basic concepts of electricity, the components that make up a photovoltaic system, and practical installation activities, so that everyone could follow the step by step.

The training, in addition to the residents who actively followed the installation of photovoltaic systems, made it possible for at least the basic concepts of photovoltaic systems to be fixed in communal understanding. Information regarding malfunctions such as heating of the battery bank conductors and audible and/or luminous warnings of the charge controller and inverter were some of the indicators passed on to the participants of the training.

The path taken indicates that the most promising means for the development of value chains in riverine communities is from the insertion of new technologies in the production process accompanied by the participation and training of the actors involved in this chain because without this integration, the transfer of technology tends to fail. Economic development is intricately linked to the social development of families, since after the installation of the system it is necessary that families are trained to handle the technology and understand its functioning and limitations.

AP4, which focused on sharing experiences and information from the project, with the objective of increasing the interest of young people and forming new leaders within the Ilha das Cinzas community and leaders from nearby communities, was executed by holding an event in early 2022, where it was possible to bring together all ATAIC partners and

community leaders interested in the community organization. The event was entitled "The social value of energy in building participatory, inclusive and sustainable communities".

From the socialization of ATAIC's experiences, other communities were able to reorganize themselves in similar ways. For example, through this event, the Association of Women Agroextractivist Producers of the Mouth of the Mazagão Velho River (AM-PAFOZ (Associação das Mulheres Produtoras Agroextrativistas da Foz do Rio Mazagão Velho)) was able to participate in the selection process for financing projects of the Honnold Foundation and be one of the few communities contemplated for the implementation of photovoltaic systems.

4. Conclusions

Based on the PRD and SWOT analysis, four action plans were elaborated:

- (1) and (2): development of a photovoltaic system capable of assuming different configurations according to the daily demands of the açaí value chain and other complementary economic activities;
- (3) training of community residents;
- (4) socialization of the experiences obtained during the execution of the project with leaders of other communities and ATAIC partner agents.

One of the main contributions of the project was the development of the photovoltaic system with versatile and flexible topology which was aligned with the weaknesses and needs of the community.

The photovoltaic system of mixed configuration has the capacity to meet domestic loads in DC and AC in the daily life of the family through the DPS and attend driving loads (removal of açaí pulp, pumping water into the reservoir, irrigation of crops with biofertilizer, crushing of seeds and nuts) through the DCPS, switching the keys to the second position, thus energizing the electric motor.

This system can contribute to the improvement of the açaí value chain in addition to enabling the integration of social technologies, both of which help in the development and autonomy of riverside communities.

In addition, this research highlights, as another contribution, the need for participation between the researcher and the community of the study area. The developed system went through three stages of improvements—all coming from responses from the community itself.

The community participation in the installation process was vital, as it enabled familiarization with this type of renewable technology, being aligned with AP3. This action plan sought to train families regarding the photovoltaic energy technology introduced in the community. Within the period of execution of this research, the action plan achieved its objective by making the installed systems more familiar to residents.

Finally, AP4 was executed with the holding of the workshop "The social value of energy in building participatory, inclusive and sustainable communities". The event was attended by leaders from different riverine and land communities interested in organizing themselves in a similar way to ATAIC and Ilha das Cinzas.

Author Contributions: Conceptualization, A.P., P.G., M.G. and A.B.; data curation, A.P., M.G., D.F., M.P. and A.B.; formal analysis, A.P., M.G. and A.B.; funding acquisition, F.M. (Francisco Malheiros), D.F., M.P. and A.B.; investigation, A.P., P.G., F.M. (Francisco Malheiros), F.M. (Felipe Monteiro), W.O., M.G., M.O., G.P., M.S., G.M., A.J., A.O., D.F. and A.B.; methodology, A.P., F.M. (Francisco Malheiros), M.G. and A.B.; project administration, A.B.; resources, M.G. and A.B.; software, A.P., F.M. (Francisco Malheiros), and F.M. (Felipe Monteiro); supervision, M.G. and A.B.; validation, A.P., F.M. (Francisco Malheiros), M.G., A.J. and A.B.; visualization, A.B.; writing—original draft, A.P.; writing—review and

editing, A.P., W.O., M.G., M.S., D.F., M.P. and A.B. All authors have read and agreed to the published version of the manuscript.

Funding: The research was developed within the scope of the projects "Solar Energy for Food Sovereignty of Riverside Families", which received external funding from the Honnold Foundation, and "Generation and Integration of Biomass and Photovoltaic Energy with the Strengthening of Productive Chains in Isolated Communities in the Amazon River Estuary". The Amazon+10 Initiative is a project of the National Council of State Research Support Foundations (Confap) and funded by the Amapá Research Support Foundation (FAPEAP) according to the public call No. 004/2022. The lead author received funding from a Master's scholarship from the Coordination for the Improvement of Higher Education Personnel (CAPES) under process No. 88887.636659/2021-00.

Institutional Review Board Statement: The research was approved by the Research Ethics Committee of the Federal University of Pará under process 3.683.904 and registered in the National System for the Management of Genetic Heritage and Associated Traditional Knowledge under code number AA34484.

Informed Consent Statement: Informed consent was obtained from all subjects involved in the study.

Data Availability Statement: The table of intersections between all SWOT matrix factors can be found in the Annexes of the main author's master's research at the link: Master's degree dissertation (available online: https://ppgca.unifap.br/wp-content/uploads/2024/07/ALLAN_GUILHERME_DISSERTACAO_FINAL.pdf (accessed on 18 February 2025)).

Conflicts of Interest: The authors declare no conflicts of interest.

References

- Araujo, R.O.; Ribeiro, F.C.P.; Santos, V.O.; Lima, V.M.R.; Santos, J.L.; Vilaça, J.E.S.; Chaar, J.S.; Falcão, N.P.S.; Pohlit, A.M.; de Souza, L.K.C. Renewable Energy from Biomass: An Overview of the Amazon Region. *Bioenergy Res.* 2022, 15, 834–849. [CrossRef]
- Franco, I.B.; Power, C.; Whereat, J. SDG 7 Affordable and Clean Energy. In Actioning the Global Goals for Local Impact; Franco, I.I., Chatterji, T., Derbyshire, E., Tracey, J., Eds.; Springer: Berlin, Germany, 2020; pp. 105–116.
- Teotónio, C.; Martins, R.; Antunes, M. Socio-Economic and environmental indicators: Do they go hand in hand or back to back? A zoom into SDG 7. *Int. J. Sustain. Energy Plan. Manag.* 2023, 38, 110–129. [CrossRef]
- De Mello Vasconcelos, O.C.; de Oliveira, W.D.; dos Santos Costa, D.; Mederos, B.J.T.; de Freitas, S.T. Artificial mango with on-board electronic and web-mobile systems to monitor in real time fruit temperature and environmental conditions. *Postharvest Biol. Technol.* 2024, 217, 113080. [CrossRef]
- Bathaei, A.; Štreimikienė, D. Renewable Energy and Sustainable Agriculture: Review of Indicators. Sustainability 2023, 15, 14307. [CrossRef]
- Da Silva, I.; Ronoh, G.; Maranga, I.; Odhiambo, M.; Kiyegga, R. Implementing the SDG 2, 6 and 7 Nexus in Kenya—A Case Study of Solar Powered Water Pumping for Human Consumption and Irrigation. In *International Business, Trade and Institutional Sustainability*; Filho, W.L., Brito, P.R.B., Frankenberger, F., Eds.; Springer: Berlin, Germany, 2020; pp. 933–942.
- Nabiyeva, G.N.; Wheeler, S.M. How Is SDG 11 Linked with Other SDGs? Evidence from the United Nations Good Practices. *Highlights Sustain.* 2024, *3*, 294–307. [CrossRef]
- Leite, C.C.; de Sousa, V. Exclusão Elétrica na Amazônia Legal: Quem ainda está sem Acesso à Energia Elétrica? Instituto de Energia e Meio Ambiente (IEMA): São Paulo, Brazil, 2020; Volume 35.
- 9. Mazzone, A. Decentralised energy systems and sustainable livelihoods, what are the links? Evidence from two isolated villages of the Brazilian Amazon. *Energy Build.* **2019**, *186*, 138–146. [CrossRef]
- 10. Pró-Açaí, D. Recomendações Para Impactos Sistêmicos na Cadeia de Valor do Açaí. Available online: https://www. dialogosproacai.org.br/acervos/dialogos-pro-acai (accessed on 1 December 2023).
- 11. Santos, E.S.; Ramos, C.A.; Guedes, M.C. Segurança alimentar de famílias extrativistas de açaí na Amazônia oriental brasileira: O caso da Ilha das Cinzas. *Novos Cad. NAEA* 2021, 24, 195–221. [CrossRef]
- 12. Suyambu, M.R.; Vishwakarma, P.K. State-of-Art Techniques for Photovoltaic (PV) Power Systems and their Impacts. *Int. J. Adv. Res. Sci. Commun. Technol.* **2024**, *4*, 381–389. [CrossRef]
- 13. Diouf, B.; Muley, A.; Pode, R. Issues, Challenges, and Future Perspectives of Perovskites for Energy Conversion Applications. *Energies* **2023**, *16*, 6498. [CrossRef]
- 14. Ponte, G.P.; Calili, R.F.; Souza, R.C. Energy generation in Brazilian isolated systems: Challenges and proposals for increasing the share of renewables based on a multicriteria analysis. *Energy Sustain. Dev.* **2021**, *61*, 74–88. [CrossRef]

- 15. Melin, M.F.M.; de Castro Camioto, F. A Importância de Incentivos Governamentais para Aumentar o Uso da Energia Solar. *Rev. Gestão Produção Operações Sist.* **2019**, *14*, 89. [CrossRef]
- Diniz, A.S.A.C.; Carlo, J.C.; Costa, S.C.S.; Kazmerski, L.L. Photovoltaics and the Built Environment in Brazil. In *Reducing the* Effects of Climate Change Using Building-Integrated and Building-Applied Photovoltaics in the Power Supply; Springer Nature: Cham, Switzerland, 2024; pp. 1–37.
- 17. Gomes, J.V.; García Sánchez, J.A. Complementos indispensáveis para a implementação apropriada da energia solar fotovoltaica como tecnologia no programa Luz para Todos. *Rev. Tecnol. Soc.* **2024**, *20*, 309. [CrossRef]
- Oliveira Martins Varella, F.K.; Vilela, I.N.R.; Gomes, R.D.M. Universalização do acesso à energia elétrica no Brasil: Panorama de SIGFIs e MIGDIs instalados. *Rev. Bras. Energ.* 2023, 29, 43–74. [CrossRef]
- 19. Mamede Filho, J. Instalações Elétricas Industriais, 9th ed.; LTC: Rio de Janeiro, Brazil, 2017.
- Meshcheryakov, V.; Belousov, A. Development of a method for reducing starting currents and electromagnetic torque of a two-phase induction motor by delaying voltage supply. In Proceedings of the 2021 XVIII International Scientific Technical Conference Alternating Current Electric Drives (ACED), Ekaterinburg, Russia, 24–27 May 2021; IEEE: Piscataway, NJ, USA, 2021; pp. 1–5.
- 21. Junior, J.S.L.; Pereira, J.I.M.; Lira, R.L. Sistema individual de Energia Elétrica com fonte intermitente fotovoltaico off grid implantada em uma habitação ribeirinha no Município de Manacapuru-AM. *Braz. J. Dev.* **2021**, *7*, 118458–118475. [CrossRef]
- 22. Trindade, A.; Verba, N.; Farias, N.; Ramon, D.; Gyamfi, K.; da Silva, H.; Viana, V. Impact Evaluation of Solar Photovoltaic Electrification: Indigenous Community Case Study in Brazilian Amazon. In Proceedings of the 9th International Conference on Sustainable Development, Bangkok, Thailand, 10–12 November 2022; p. 16.
- De Sousa, M.C.; Batista, L.M.; Fiel, L.G.; Monteiro Neto, A.; Freitas, K.M.; da Silva Pereira, R.; Marques, G.T.; Chase, O.A. Sistema Fotovoltaico Off Grid para comunidade ribeirinha na Região Insular de Belém-Pará. *Rev. Ibero-Am. Ciências Ambient.* 2021, 12, 312–324. [CrossRef]
- 24. Torres, N.N.S.; Ledesma, J.J.G.; Cavallari, M.R.; Ando Junior, O.H. Amazon Kit: Proposal for an Innovative Energy Generation and Storage Solution for Sustainable Development of Isolated Communities. *Sustainability* **2024**, *16*, 6280. [CrossRef]
- 25. Fey, A.N.; Leite, V.; Ribeiro Romaneli, E.F. A Low Power Photovoltaic Water Pumping System based on a DC-DC Step-up Converter and Standard Frequency Converters. In Proceedings of the 2020 9th International Conference on Renewable Energy Research and Application (ICRERA), Glasgow, UK, 27–30 September 2020; IEEE: Piscataway, NJ, USA; pp. 138–143.
- Alili, A.; Flamand, N.; Frappé, E.; Jebai, A.K. Direct PV Array Connection with Variable Speed Drive and MPPT Control Strategy. In Proceedings of the 2023 IEEE 8th Southern Power Electronics Conference and 17th Brazilian Power Electronics Conference (SPEC/COBEP), Florianopolis, Brazil, 26–29 November 2023; IEEE: Piscataway, NJ, USA, 2023; pp. 1–6.
- 27. Gasque, M.; González-Altozano, P.; Gutiérrez-Colomer, R.P.; García-Marí, E. Comparative evaluation of two photovoltaic multipump parallel system configurations for optimal distribution of the generated power. *Sustain. Energy Technol. Assess.* **2021**, *48*, 101634. [CrossRef]
- 28. Queiroz, A.O.; Brito, A.U. Direct Connection Photovoltaic System in Multi-Motor Application for the Rural Sector. *Eng. Agrícola* **2020**, 4430, 303–314. [CrossRef]
- 29. Feijão, A.T.; Almeida, A.M.G.; Brito, A.U. Photovoltaic acai (*Euterpe oleracea* Mart.) berry juice extractor machine. *J. Phys. Conf. Ser.* **2022**, *2180*, 012004. [CrossRef]
- Zucoloto, G.F.; Pereira, L.S. Tecnologias Sociais E Economia Solidária: Projetos Certificados Pela Fundação Banco do Brasil. In Dinâmicas da Economia Solidária no Brasil: Organizações Econômicas, Representações Sociais e Políticas Públicas; Silva, P.S., Ed.; Instituto de Pesquisa Econômica Aplicada (IPEA): Brasília, Brazil, 2020; pp. 187–205. [CrossRef]
- 31. Cerqueira, L. *Guia do Diagnóstico Participativo*, 2nd ed.; FLACSO: Brasília, Brasil, 2021. Available online: https://biblioteca.flacso. org.br/?publication=guia-do-diagnostico-participativo (accessed on 3 June 2022).
- 32. Ventura, K.S.; Suquisaqui, A.B.V. Aplicação de ferramentas SWOT e 5W2H para análise de consórcios intermunicipais de resíduos sólidos urbanos. *Ambiente Construído* 2020, 20, 333–349. [CrossRef]
- 33. Filho, T.A.G.; Júnior, A.S.S.; Ferreira, A.B.S.; Silva, V.L.; Santos, A.M.; Santos, J.L.D.M.; Marques, F.R.V.; De Oliveira, K.C.; Caldeira, F.M.; Chagas, A.M.; et al. Matriz SWOT Como Ferramenta Estratégica Na Gestão De Instituições De Ensino: Implicações Para O Processo De Ensino E Aprendizagem. Usiness Manag. 2024, 26, 1–6.
- 34. Martins, F. Promoção da Saúde em Comunidades Isoladas Através do Abastecimento de Energia. 2024. Available online: https://jornal.usp.br/?p=818139 (accessed on 19 November 2023).
- 35. Da Silva, B.N. Ferramentas Adicionais ao Projeto de Sistemas Fotovoltaicos Isolados Para Unidades Familiares Ribeirinhas: Uma Experiência na Comunidade de Ilha das Cinzas-Gurupá, PA. Master's Thesis, Universidade Federal do Pará, Belém, Brazil, 2018. Available online: www.tcpdf.org (accessed on 1 August 2021).
- Ferrareze Feitosa, M. Índice de eficiência microbiológica de uma fossa séptica biodigestora. *Rev. Ciência Tecnol. Fatec Lins* 2024, 10, 266–279. [CrossRef]

- Barony, F.; Luz, L.; Santos, E.C.d.S.; Júnior, J.C.A.; Fernandes, E. Efeito de Efluente Sanitário Tratado por Fossa Séptica Biodigestora no Crescimento de Mudas de Couve. In Proceedings of the XV Congresso Brasileiro de Gestão Ambient, Belém, Brazil, 8 November 2024.
- Instituto SENAI de Inovação em Energias Renováveis, Senado Federal, Ministério de Ciência Tecnologia e Inovação (Brazil). Atlas Solar Estado Amapá; ISI-ER: Natal, Brazil, 2024; p. 142.
- 39. MINASOL. Módulo Fotovoltaico Policristalino MS320; MINASOL Painés Fovoltaicos: Araguari, Brazil, 2021.
- Peroza, J.; Krenzinger, A.; De Aguiar, D. Ruptura por Avalanche em Células Fotovoltaicas e suas Implicações em Análises de Associações no Software Crearray. In Anais do VII Congresso Brasileiro de Energia Solar (CBENS), VII CBENS, Gramado, Brazil, 17–20 April 2018; ABENS: Gramado, Brazil, 2018.
- Pena, A.G.L.; Brito, A.U.; Guedes, P.M.L.; Monteiro, F.; Malheiros, J.B.; Malheiros, F.B.; Guedes, M.C.; Júnior, A.F.D.; François, D.E.; Poganietz, W.-R.; et al. Sistema Fotovoltaico Isolado de Configuração Mista Para Famílias Ribeirinhas. *Rev. Bras. Energ. Sol.* 2022, 13, 203–212. Available online: https://rbens.emnuvens.com.br/rbens/article/view/399 (accessed on 3 April 2023).
- Integral Tecnologia. Inversor de Frequência de Energia Solar para Motores-1.5 CV; 3 CV; 5 CV-Modelos IVS100-Manual de Instruções-V2.0; Integral Sistemas Eletrônicos Eireli: Porto Alegre, Brazil, 2021; pp. 3–6. Available online: https://www.integraltec.com.br/drive-solar-1-5cv (accessed on 23 June 2022).

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.